

US009636073B2

US 9,636,073 B2

May 2, 2017

(12) United States Patent

Evans et al.

(54) DUAL-MODALITY MAMMOGRAPHY

(71) Applicant: CAPERAY MEDICAL (PTY) LTD,

Cape Town (ZA)

(72) Inventors: Michael David Evans, Fish Hoek

(ZA); Raphael V. Smith, Observatory (ZA); Christopher Leonard Vaughan,

Newlands (ZA)

(73) Assignee: CAPERAY MEDICAL (PTY) LTD.

(ZA)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 363 days.

(21) Appl. No.: 14/136,775

(22) Filed: Dec. 20, 2013

(65) Prior Publication Data

US 2014/0180082 A1 Jun. 26, 2014

(30) Foreign Application Priority Data

Dec. 21, 2012	(ZA)	 201209726
Jun. 21, 2013	(GB)	 1311124.0

(51) Int. Cl.

A61B 6/00 (2006.01)

A61B 8/00 (2006.01) (Continued)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

CPC A61B 6/025; A61B 6/0414; A61B 6/488; A61B 6/502; A61B 6/5247; A61B 8/0825;

(Continued)

(56) References Cited

(45) Date of Patent:

(10) Patent No.:

U.S. PATENT DOCUMENTS

3,480,002 A 3,964,296 A 11/1969 Flaherty et al. 6/1976 Matzuk (Continued)

FOREIGN PATENT DOCUMENTS

DE 19837259 3/2000 DE 19901730 A 7/2000 (Continued)

OTHER PUBLICATIONS

Co-Pending Application No. EP 2577279, File History dated Sep. 2, 2015, 87 pages.

(Continued)

Primary Examiner — Ruth S Smith (74) Attorney, Agent, or Firm — New River Valley IP Law, PC; Michele L. Mayberry

(57) ABSTRACT

A scanning assembly for a dual-modality automated biological tissue imaging device having first and second compression surfaces is provided. The assembly comprises a housing defining a scanning/compression surface, an ultrasonic transducer mounted within the housing adjacent the scanning surface for movement in a plane parallel to the scanning surface and imaging the tissue through the scanning surface, an X-ray detector mounted within the housing for forming an X-ray image of the tissue based on X-ray radiation passed through the tissue and scanning surface from an X-ray source, and a drive for moving the transducer across the scanning surface so that the transducer generates a plurality of two-dimensional ultrasound tissue images. The housing is hermetically sealed and filled with non-conductive fluid with acoustic impedance resembling that of the tissue. The scanning surface has acoustic impedance resembling that of the tissue and can substantially withstand compression forces applied to the tissue.

11 Claims, 8 Drawing Sheets

